

SELEX

BATTEN FITTING- MX SERIES



Product Features

- High Quality LED Tube
- Steel base with high Luminous efficiency
- Innovative design , Simple installation
- Low Power Consumption

Application

- Supermarket
- Shopping Mall
- Restaurants
- School
- Parking Lot

Advantages

- 80% Energy Saving
- Environmentally Safe
- Less Heat produced
- Zero UV Emission



TECHNICAL DATA

Product Code	LSB110-MX	LSB210-MX	LSB120-MX	LSB220-MX
Power	1X10W	2X10W	1X20W	2X20W
Voltage	220-240V AC	220-240V AC	220-240V AC	220-240V AC
Luminous Flux*	1000 Lm	2000 Lm	2000 Lm	4000 Lm
Efficacy	100 Lm/W	100 Lm/W	100 Lm/W	100 Lm/W
Energy efficiency	A+	A+	A+	A+
Net weight	0.51 Kg	0.63 Kg	0.935 Kg	1.15 Kg
CRI	> 80	> 80	> 80	> 80
Beam angle	220°	220°	220°	220°
Operating temperature	-20 °C to+40 °C	-20 °C to+40 °C	-20 °C to+40 °C	-20 °C to+40 °C
Storage temperature	Up to 50°C	Up to 50°C	Up to 50°C	Up to 50°C
Body Material	Steel body	Steel body	Steel body	Steel body
CCT	3000K / 6500K	3000K / 6500K	3000K / 6500K	3000K / 6500K
IP	20	20	20	20
Dimmable	No	No	No	No
Life Time	30,000Hrs	30,000Hrs	30,000Hrs	30,000Hrs
Cover	No Cover	No Cover	No Cover	No Cover
Finishing color	White	White	White	White
Mounting	Surface/ Hanging	Surface/ Hanging	Surface/ Hanging	Surface/ Hanging
Size in mm (LXWXH)	625X50X35	625X50X35	1230X50X35	1230X50X35

*Lumen may change subject to lamp wattage

