



LED GLASS TUBE



Product Features

High Quality & Performance
LED Glass Tube
Built in Driver, Mercury Free
Flicker Free, No UV & IR


Application

For all compatible
Lamp fittings

Advantages

80% Energy Saving
Environmentally Safe
Less Heat produced
Zero UV Emission


Energising Tomorrow



TECHNICAL DATA

Product Code	LST-T8-10G	LST-T8-20G	LST-T8-24G
Power	10W (2Ft)	20W (4Ft)	24W (5Ft)
Voltage	220-240V AC	220-240V AC	220-240V AC
Luminous Flux*	1000 Lm	2000 Lm	2400 Lm
Efficacy	100 Lm/W	100 Lm/W	100 Lm/W
Energy efficiency	A+	A+	A+
Net weight	0.115 Kg	0.22 Kg	0.25 Kg
CRI	> 80	> 80	> 80
Beam angle	280°	280°	280°
Operating temperature	-20 °C to+40 °C	-20 °C to+40 °C	-20 °C to+40 °C
Storage temperature	Up to 50°C	Up to 50°C	Up to 50°C
Body Material	Glass Body	Glass Body	Glass Body
CCT	3000K / 6500K	3000K / 6500K	3000K / 6500K
IP	20	20	20
Dimmable	No	No	No
Life Time	30,000Hrs	30,000Hrs	30,000Hrs
Cover	No	No	No
Finishing color	White	White	White
Base	G13	G13	G13
Size in mm (LXWXH)	604X25.4	1214X25.4	1510X25.4

*Lumen may change subject to lamp wattage



LST-T8-10G

LST-T8-20G

LST-T8-24G

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM

