



WATERPROOF LIGHT FITTING- DX SERIES NOVO PLUS



Product Features


- High Quality LED Tube
- Anti UV and Flame retardance
- Lamp Base equipped with wire protective rings and water proof glands
- Sealing Clips - Steel Clips
- Lead wire Size - H05RNF3 x 1.5mm²

Application

- Car Park Lighting
- Ware houses & Storage
- Electrical &
- Plumbing Rooms
- Body Work shops
- Garages, Factory

Advantages

- 80% Energy Saving
- Environmentally Safe
- Less Heat produced,
- Zero UV Emission,
- 100% Poly Carbonate body for non-breakage & durability



TECHNICAL DATA

Product Code	LSW110-DX	LSW210-DX	LSW120-DX	LSW220-DX
Power	1X10W	2X10W	1X20W	2X20W
Voltage	220-240V AC	220-240V AC	220-240V AC	220-240V AC
Luminous Flux*	1000 Lm	2000 Lm	2000 Lm	4000 Lm
Efficacy	100 Lm/W	100 Lm/W	100 Lm/W	100 Lm/W
Energy efficiency	A+	A+	A+	A+
Net weight	0.905 Kg	1.260 Kg	1.675 Kg	2.32 Kg
CRI	> 80	> 80	> 80	> 80
Beam angle	220°	220°	220°	220°
Operating temperature	-20 °C to+40 °C	-20 °C to+40 °C	-20 °C to+40 °C	-20 °C to+40 °C
Storage temperature	Up to 50°C	Up to 50°C	Up to 50°C	Up to 50°C
Body Material	Poly Carbonate	Poly Carbonate	Poly Carbonate	Poly Carbonate
CCT	3000K / 6500K	3000K / 6500K	3000K / 6500K	3000K / 6500K
IP	65	65	65	65
Dimmable	No	No	No	No
Life Time	30,000Hrs	30,000Hrs	30,000Hrs	30,000Hrs
Cover	Clear Cover	Clear Cover	Clear Cover	Clear Cover
Finishing color	Black	Black	Black	Black
Mounting	Surface/ Hanging	Surface/ Hanging	Surface/ Hanging	Surface/ Hanging
Size in mm (LXWXH)	655X80X84	655X120X84	1260X80X84	1260X120X84

*Lumen may change subject to lamp wattage

