



## D2 DOWN LIGHT

SLD-8-SMD-D2

### Product Description

WAVE tunable white LED down light adopts dual-color temp SMD complying to DT8 standard; With Dual DALI driver which meets DALI2 standard. PC diffuser with even light output. White, silver, chrome surface treatment are available for customer's preference.

### Application Area

It is designed for general lighting applications in office, supermarket, shop, school, hotel, etc. It is also widely used for public areas, such as stairway, lobby, reception, corridors etc.

### Certifications

- CE
- RoHS

### Options

COLOUR TEMPERATURE	3000K-6500K
BODY FINISH	WHITE
DIMMING CONTROL	DALI & 0-10V

### Basic Details

WATTAGE	12W,15W,18W,25W,30W
COLOUR TEMPERATURE	3000K-6500K
LUMEN/WATT	100lm/W
INPUT VOLTAGE	AC200-240V
FREQUENCY	50HZ
POWER FACTOR	>0.9
IP RATING	IP54
CRI	>80
MATERIAL	ALUMINIUM & PC
BODY FINISH	WHITE
LIFE HOURS	40000
LED CHIP	SMD

### Mounting Information

PRODUCT CODE	PDNL12W-US	PDNL15W-US
Available Wattage	12	15
Size Cutout	100-110	120-130
Outer Dia	Dia 120 x45	Dia 145x45

PDNL18W-US	PDNL25W-US	PDNL30W-US
18	25	30
200-210	200-210	200-210
Dia228x45	Dia228x45	Dia228x45

