



MONO SURFACE LIGHT

PSL-6M-CN , PSL-12M-CN ,
PSL-18M-CN , PSL-24M-CN

Product Description

Introducing the "Mono" Surface Light series: where durability meets elegance. Crafted with die-cast aluminium and a sleek diffuser, it ensures longevity and uniform light distribution. Effortless installation with built-in driver and integrated design. Available in white and black to complement any decor. With screw-less mounting, installation is quick and hassle-free. Illuminate your space with ease and sophistication.

Application Area

living rooms, bedrooms, kitchens, bathrooms, offices, hallways, retail stores, restaurants, and other indoor spaces.

Mounting Information

Product Code	PSL-6M-CN	PSL-12M-CN	PSL-18M-CN	PSL-24M-CN
Available Wattage (W)	6	12	18	24
Dimension	Dia 90xH57mm	Dia 120xH58mm	Dia 140xH58mm	Dia 180xH65mm

Basic Details

WATTAGE	6 , 12 , 18 , 24W
COLOUR TEMPERATURE	4000K
LUMEN/WATT	69.71lm/W, 85.17lm/W 86.05lm/W 97.79lm/W.
INPUT VOLTAGE	AC220-240V
FREQUENCY	50/60Hz
POWER FACTOR	0.5
IP RATING	Ip20
OPERATING TEMPERATURE	-20°C TO +40°C
DIMMABLE	NO
CRI	>80
MATERIAL	ALUMINIUM
BODY FINISH	WHITE/BLACK
LAMP TYPE	SMD
LIFE HOURS	30000HRS
LED CHIP	SANAN
BEAM ANGLE	110°*
IK RATING	IK06
MOUNTING	SURFACE

Light Distribution Diagram

