



SUM SURFACE LIGHT

PSL15S-US

Product Description

SUM Surface mounted downlight adopts straightforward design with stylish appearance, easy to install. The lamp adopts high quality reflector which has good reflective rate and light output > 86%. AL6063 Aluminum body with oxidation treatment provides corrosion resistance and excellent heat dissipation performance. LEDs are high lumen COB chip with CRI>80. Built-in driver is independent and replaceable, which is friendly maintenance. PF>0.9, THD<20%, passed EMC test with strong anti-jamming capability. Besides, it possesses short-circuit protection and overvoltage protection function, showing high safety performan

Application Area

Downlight is designed for general lighting applications in hotel, home, office, shop etc. It is also widely used for public areas such as stairway, lobby, reception, corridors etc

Certifications

- CE
- RoHS

Mounting Information

Product Code	PSL15S-US	PSL20S-US	PSL25S-US	PSL32S-US
Available Wattage (W)	15	20	25	32
Dimmension	Dia 120 x 110	Dia 120 x 110	Dia 120 x 110	Dia 160 x 120

Basic Details

WATTAGE	15, 20 , 25 , 32W
COLOUR TEMPERATURE	2700-6500K
LUMEN/WATT	100lm/W
INPUT VOLTAGE	220-240V
FREQUENCY	50-60HZ
POWER FACTOR	>0.9
IP RATING	Ip54
CRI	>80
MATERIAL	ALUMINIUM BODY
BODY FINISH	WHITE
LIFE HOURS	50000

Options

COLOUR TEMPERATURE	2700-6500K
DIMMING CONTROL	TIAC , DALI.
BEAM ANGLE	24,36,45,60

Mounting Information

