



## RUMIA SURFACE LIGHT

PSL15R-US

### Product Description

This new surface mounted downlight has a complete size options, it has faceted and specular reflector design for different optic reflection. Screw less on surface and tempered glass in front part, which offer a better appearance, high protection level and convenient installation. Two options for optic combination: Type A COB LED chip+lens+reflector, Type B SMD LED chip+diffuser+reflector.

#### Application Area

It is designed for general lighting applications in Retails, conference rooms, hotels, restaurants, Foyers, corridors, and living spaces, etc...

### Certifications

- CE
- RoHS

### Basic Details

WATTAGE	15 , 25 , 30W
COLOUR TEMPERATURE	3000,4000,6500K
LUMEN/WATT	110lm/W
INPUT VOLTAGE	AC200-240V
FREQUENCY	50/60HZ
POWER FACTOR	>0.9
IP RATING	Ip65
CRI	>80
MATERIAL	IRON WITH TEMPERED GLASS
BODY FINISH	WHITE AND BLACK
LIFE HOURS	50000HRS
LED CHIP	COBUGR<19
IK RATING	IK06

### Options

COLOUR TEMPERATURE	3000,4000,6500K
DIMMING CONTROL	TRIAC AND DALI
BEAM ANGLE	24,36,60

### Mounting Information

Product Code	PSL15R-US	PSL25R-US	PSL30R-US
Available Wattage (W)	15	25	30
Dimmension	Dia 90xH107	Dia 130xH115	Dia 160xH110