



### **IMPERIA** SURFACE LIGHT

PSL18I-JK , PSL32I-JK

## **Product Description**

Introducing the IMPERIA series Surface Light: Setting new standards with its ultra-thin design, offering uniform and soft illumination. Built to withstand outdoor elements, boasting IP55 and IK08 ratings with a durable PP housing and cover. Seamlessly integrated with a built-in driver for streamlined functionality. Available in elegant white, effortlessly complements any space. IMPERIA series ensures hassle-free setup and reliable, adaptable lighting solutions for both indoor and outdoor environments.

#### **Application Area**

It is designed for general lighting applications in office, supermarket, shop, school, hotel, etc. It is also widely used for reception, Showrooms etc.

# Certifications

- CE
- RoHS
- CB

# **Mounting Information**

PRODUCT CODE	PSL18I-JK	PSL32I-JK
AVAILABLE WATTAGE	13-18W	22-32W
SIZE	Dia 360 x 25mm	Dia 410 x 25mm

### **Basic Details**

WATTAGE 13-18W,22 - 32W (Switchable Wattage)  COLOUR TEMPERATURE 3000K/4000K/6500K  LUMEN/WATT 120lm/W  INPUT VOLTAGE AC 220-240V  FREQUENCY 50/60Hz  DRIVER CURRENT 130/240mA  POWER FACTOR >0.9  IP RATING IP65  OPERATING TEMPERATURE -20* TO +40*C  CRI >90  MATERIAL PP / ALUMINIUM  BODY FINISH WHITE / BLACK  LIFE HOURS 50000Hrs  BEAM ANGLE 120*  IK RATING IK08  LED TYPE SMD2835  DRIVER BUILT IN NON -ISOLATED  DIMMABLE NO			
LUMEN/WATT         120lm/W           INPUT VOLTAGE         AC 220-240V           FREQUENCY         50/60Hz           DRIVER CURRENT         130/240mA           POWER FACTOR         >0.9           IP RATING         IP65           OPERATING TEMPERATURE         -20* TO +40*C           CRI         >90           MATERIAL         PP / ALUMINIUM           BODY FINISH         WHITE / BLACK           LIFE HOURS         50000Hrs           BEAM ANGLE         120*           IK RATING         IK08           LED TYPE         SMD2835           DRIVER         BUILT IN NON -ISOLATED	WATTAGE	13-18W,22 - 32W (Switchable Wattage)	
INPUT VOLTAGE  AC 220-240V  FREQUENCY  50/60Hz  DRIVER CURRENT  130/240mA  POWER FACTOR  >0.9  IP RATING  IP65  OPERATING TEMPERATURE  -20* TO +40*C  CRI  >90  MATERIAL  PP / ALUMINIUM  BODY FINISH  WHITE / BLACK  LIFE HOURS  50000Hrs  BEAM ANGLE  120*  IK RATING  IK08  LED TYPE  SMD2835  DRIVER	COLOUR TEMPERATURE	3000K/4000K/6500K	
FREQUENCY 50/60Hz  DRIVER CURRENT 130/240mA  POWER FACTOR >0.9  IP RATING IP65  OPERATING TEMPERATURE -20* TO +40*C  CRI >90  MATERIAL PP / ALUMINIUM  BODY FINISH WHITE / BLACK  LIFE HOURS 50000Hrs  BEAM ANGLE 120*  IK RATING IK08  LED TYPE SMD2835  DRIVER BUILT IN NON -ISOLATED	LUMEN/WATT	120lm/W	
DRIVER CURRENT         130/240mA           POWER FACTOR         >0.9           IP RATING         IP65           OPERATING TEMPERATURE         -20* TO +40*C           CRI         >90           MATERIAL         PP / ALUMINIUM           BODY FINISH         WHITE / BLACK           LIFE HOURS         50000Hrs           BEAM ANGLE         120*           IK RATING         IK08           LED TYPE         SMD2835           DRIVER         BUILT IN NON -ISOLATED	INPUT VOLTAGE	AC 220-240V	
POWER FACTOR >0.9  IP RATING IP65  OPERATING TEMPERATURE -20* TO +40*C  CRI >90  MATERIAL PP / ALUMINIUM  BODY FINISH WHITE / BLACK  LIFE HOURS 50000Hrs  BEAM ANGLE 120*  IK RATING IK08  LED TYPE SMD2835  DRIVER BUILT IN NON -ISOLATED	FREQUENCY	50/60Hz	
IP RATING IP65  OPERATING TEMPERATURE -20* TO +40*C  CRI >90  MATERIAL PP / ALUMINIUM  BODY FINISH WHITE / BLACK  LIFE HOURS 50000Hrs  BEAM ANGLE 120*  IK RATING IK08  LED TYPE SMD2835  DRIVER BUILT IN NON -ISOLATED	DRIVER CURRENT	130/240mA	
OPERATING TEMPERATURE  -20* TO +40*C  CRI >90  MATERIAL PP / ALUMINIUM  BODY FINISH WHITE / BLACK  LIFE HOURS 50000Hrs  BEAM ANGLE 120*  IK RATING IK08  LED TYPE SMD2835  DRIVER BUILT IN NON -ISOLATED	POWER FACTOR	>0.9	
CRI >90  MATERIAL PP / ALUMINIUM  BODY FINISH WHITE / BLACK  LIFE HOURS 50000Hrs  BEAM ANGLE 120*  IK RATING IK08  LED TYPE SMD2835  DRIVER BUILT IN NON -ISOLATED	IP RATING	IP65	
MATERIAL PP / ALUMINIUM  BODY FINISH WHITE / BLACK  LIFE HOURS 50000Hrs  BEAM ANGLE 120*  IK RATING IK08  LED TYPE SMD2835  DRIVER BUILT IN NON -ISOLATED	OPERATING TEMPERATURE	-20* TO +40*C	
BODY FINISH  WHITE / BLACK  LIFE HOURS  50000Hrs  BEAM ANGLE  120*  IK RATING  IK08  LED TYPE  SMD2835  DRIVER  BUILT IN NON -ISOLATED	CRI	>90	
LIFE HOURS 50000Hrs  BEAM ANGLE 120*  IK RATING IK08  LED TYPE SMD2835  DRIVER BUILT IN NON -ISOLATED	MATERIAL	PP / ALUMINIUM	
BEAM ANGLE 120*  IK RATING IK08  LED TYPE SMD2835  DRIVER BUILT IN NON -ISOLATED	BODY FINISH	WHITE / BLACK	
IK RATING IK08  LED TYPE SMD2835  DRIVER BUILT IN NON -ISOLATED	LIFE HOURS	50000Hrs	
LED TYPE SMD2835  DRIVER BUILT IN NON -ISOLATED	BEAM ANGLE	120*	
DRIVER BUILT IN NON -ISOLATED	IK RATING	IK08	
	LED TYPE	SMD2835	
DIMMABLE NO	DRIVER	BUILT IN NON -ISOLATED	
	DIMMABLE	NO	

# **Mounting Information**



