



## DRYGLO WATERPROOF FITTING

- \* PWP-D40-DX-1 \*PWP-D40-DX2
- \* PWP-D40-DX3

### Product discription

Introducing Dryglo: The ultimate triproof lighting solution, built with a durable PC housing and stainless steel clips for robust performance in challenging environments. With IP65 protection, Dryglo is ideal for outdoor and industrial use, providing unparalleled illumination and durability where it's needed most. Illuminate your spaces confidently with Dryglo's reliable design and superior performance, ensuring safety and visibility in any setting.

#### Application Area

- Car Parking
- Warehouses
- Storage
- Electrical & Plumbing Rooms
- Body Workshops
- Garages
- Factory.

### Certifications

- CE
- CB
- ROHS
- IP

### Options

BODY FINISH	WHITE
BEAM ANGLE	220*
COLOUR TEMPERATURE	6500K

### Basic details

WATTAGE	40W
COLOUR TEMPERATURE	6500K
LUMINOUS FLUX/WATT	100lm/W
LUMINOUS FLUX	4000lm
INPUT VOLTAGE	220-240V AC
FREQUENCY	50/60HZ
INPUT CURRENT	<0.3A
OUTPUT CURRENT	350mA
WORKING TEMPERATURE	-10°C - +50°C
OVERLOAD PROTECTION	YES
SHORT CIRCUIT PROTECTION	YES
DIMMABLE	NON DIMMABLE
MOUNTING	SURFACE MOUNTED
LOCATION	CEILING / WALL
POWER FACTOR	>0.9
CRI	>80
MATERIAL	ABS BODY + CLIPS
COVER	PC DIFFUSER
THD	<15%
FINISHING COLOR	WHITE
LIFE HOURS	54000
STARTUP TIME	<0.5s
BEAM ANGLE	220*
LED TYPE	SMD 2835
IP RATING	Ip65
FLICKER	NO
DRIVER	LIFUD
IK RATING	10
ENVIRONMENT	INDOOR / OUTDOOR
PROTECTION CLASS	1

#### Optional Driver

* TRIDONIC
* LIFUD
* SELEX DRIVER & SENSOR
1265 x 88 x 130mm