

SELEX

DUSTPROOF LIGHT FITTING- MX SERIES



Product Features

Prismatic Diffuser- High Quality PS Material
Anti Corrosion and High Mechanical Strength
Lamp Base equipped with wire protective rings and water proof glands
Suitable for Embedded installation
Base 0.5mm die-formed cold rolled steel

Application

House rooms
Classrooms
Plant Rooms
Luxurious Hotels
Supermarkets

Advantages

80% Energy Saving
Environmentally Safe
Less Heat produced
Innovative , Easy installation and long Life



TECHNICAL DATA

| Product Code | LSD110-MX | LSD210-MX | LSD120-MX | LSD220-MX |
|-----------------------|----------------------------|------------------|----------------------------|------------------|
| Power | 1X10W | 2X10W | 1X20W | 2X20W |
| Voltage | 220-240V AC | 220-240V AC | 220-240V AC | 220-240V AC |
| Luminous Flux* | 1000 Lm | 2000 Lm | 2000 Lm | 4000 Lm |
| Efficacy | 100 Lm/W | 100 Lm/W | 100 Lm/W | 100 Lm/W |
| Energy efficiency | A+ | A+ | A+ | A+ |
| Net weight | 0.73 Kg | 1.000 Kg | 1.245 Kg | 1.820 Kg |
| CRI | > 80 | > 80 | > 80 | > 80 |
| Beam angle | 140° | 140° | 140° | 140° |
| Operating temperature | -20 °C to+40 °C | -20 °C to+40 °C | -20 °C to+40 °C | -20 °C to+40 °C |
| Storage temperature | Up to 50°C | Up to 50°C | Up to 50°C | Up to 50°C |
| Body Material | Power coated metallic Body | | Power coated metallic Body | |
| CCT | 3000K / 6500K | 3000K / 6500K | 3000K / 6500K | 3000K / 6500K |
| IP | 20 | 20 | 20 | 20 |
| Dimmable | No | No | No | No |
| Life Time | 30,000Hrs | 30,000Hrs | 30,000Hrs | 30,000Hrs |
| Cover | Prismatic | Prismatic | Prismatic | Prismatic |
| Finishing color | White | White | White | White |
| Mounting | Surface/ Hanging | Surface/ Hanging | Surface/ Hanging | Surface/ Hanging |
| Size in mm (LXWXH) | 630X100X65 | 630X163X65 | 1240X100X65 | 1240X163X65 |

*Lumen may change subject to lamp wattage

