



LED FLOOD LIGHT



Product Features

- Self Maintained Diode
- Mercury free
- Integrated design, built-in Driver
- No UV & IR radiation
- L70 - 30,000Hrs

Application

- Warehouse
- Boundary Wall
- Path way

Advantages

- 80% Energy Saving
- Environmentally Safe
- Less Heat produced
- Innovative , Easy installation and long Life



Energising Tomorrow




TECHNICAL DATA

Product Code	SGLF 50W	SGLF 100W	SGLF 150W	SGLF 200W	SGLF 300W
Power	50W	100W	150W	200W	300W
Voltage	220-240V AC	220-240V AC	220-240V AC	220-240V AC	220-240V AC
Luminous Flux	5000 Lm	10000 Lm	15000 Lm	20000 Lm	30000 Lm
Efficacy	100 Lm/W	100 Lm/W	100 Lm/W	100 Lm/W	100 Lm/W
Energy efficiency	A+	A+	A+	A+	A+
Net weight	1.88 Kg	3.25 Kg	4.845 Kg	5.055 Kg	7.505 Kg
CRI	> 80	> 80	> 80	> 80	> 80
Beam angle	120°	120°	120°	120°	120°
Operating temperature	-10 °C to+40 °C	-10 °C to+40 °C	-10 °C to+40 °C	-10 °C to+40 °C	-10 °C to+40 °C
Storage temperature	Up to 50°C	Up to 50°C	Up to 50°C	Up to 50°C	Up to 50°C
Body Material	Aluminium Body	Aluminium Body	Aluminium Body	Aluminium Body	Aluminium Body
CCT	3000K / 6500K	3000K / 6500K	3000K / 6500K	3000K / 6500K	3000K / 6500K
IP	66	66	66	66	66
Dimmable	No	No	No	No	No
Life Time	30,000Hrs	30,000Hrs	30,000Hrs	30,000Hrs	30,000Hrs
Cover	Clear Tempered Glass			Clear Tempered Glass	
Finishing color	Grey	Grey	Grey	Grey	Black
Mounting	Surface/ Hanging	Surface/ Hanging	Surface/ Hanging	Surface/ Hanging	Surface/ Hanging
Size in mm (LXWXH)	280X270X60	280X270X60	350X320X100	350X320X100	420X380X90

SGLF 50W



SGLF 200W



SGLF 100W



SGLF 150W



SGLF 300W

