



UFO HIGH BAY LIGHT - PROLIGHT



Product Features


- Modern Aluminum Housing
- Economic Design
- Integrated design, built-in Driver
- Class II Electrical protection

Application

Workshop, Warehouse,
Toll station, Gas station,
Freezers, Supermarket,
Parking place, Exhibition hall,
Gymnasium, Shipyard etc.

Advantages

- 80% Energy Saving
- Environmentally Safe
- Less Heat produced
- Surface/ Hanging Mounted



TECHNICAL DATA

Product Code	SHB-150W- PRO
Power	150 W
Voltage	220-240 AC
Luminous Flux	22500 Lm
Efficacy	150 Lm/W
Energy efficiency	A+
Input current	1.6 A
CRI	> 80
Power factor	>0.95
UGR	<30
SDCM	<3
LED	Samsung
Driver	MOSO
Certificates	L80B50, IK08
Net weight	2.6 Kg
Beam angle	60° , 90° , 120°
Operating temperature	-40 °C to+55 °C
Storage temperature	Up to 60°C
Body Material	Die cast Aluminium
CCT	5700K
IP	66
Dimmable	No
Life Time	80,000Hrs
Cover	Frosted PC diffuser
Finishing color	Black
Mounting	Surface/ Hanging
Size in mm (LXWXH)	320X165

Energising Tomorrow

