



ENCLOSED WEATHERPROOF ISOLATOR



Features:

- Rated operational voltage U_e : 240/440V
- Rated insulation voltage U_i : 690V
- Rated operational current I_e : 20A, 35A, 45A & 63A
- Rated insulation voltage U_i : 690V
- No. of pole: 2P, 3P, 4P
- Protection degree: IP66
- Rated impulse withstand voltage U_{imp} : 2.5kV
- Rated frequency: 50/60 Hz
- Rated utilization category: AC-23A
- Rated making capacity: 10 Ie
- Rated breaking capacity: 10 Ie
- Rated short-time withstand current I_{cw} : 12I, 1s
- Rated short-circuit making capacity I_{cm} : 20 Ie
- Pollution degree: 3
- Suitable for surface mounting
- Standard specification: IEC60947-3 & BS EN 60947-3



Model	Pole	Current(A)	Carton Qty
SIW-D20	2	20	40
SIW-D35	2	35	40
SIW-D45	2	45	40
SIW-D63	2	63	40
SIW-T20	3	20	40
SIW-T35	3	35	40
SIW-SD45	3	45	40
SIW-T63	3	63	40



Switch-Isolators from Selex-J Series are sturdily built to withstand more than just the vagaries of the weather. The entire range of Selex Isolating switches are exclusively designed to surpass uncompromising standards of total safety and reliability.

When safety and quality matter most, choose Selex. It's the logical choice.

UNIQUE FEATURE

- Selex Isolators are uniquely designed to be compact and neat in appearance - coupled with Selex renowned standard of quality, this allows the product to be placed unobtrusively in any outdoor location, no matter how exposed it is to the harsh effects of extreme heat, dust, rain and humidity.
- The polycarbonate front cover has been deliberately chosen to withstand the rigours of outdoor environments.
- All models are weatherproof as per IP66 and tested to IEC 60947-3 and BS EN 60947-3.
- An important point to note is that Selex Isolators are independently tested by renowned independent test authority, besides our own in-house testing.

Energying Tomorrow