



LED BULKHEAD LIGHT



LBHR-20W-BK



LBHR-20W-WH



LBHO-20W-BK



LBHO-20W-WH

Product Features

Thermal Conductive Plastic Coated
Poly carbonate Body
Heat Resistant Diffuser
Integrated design, built-in Driver
Class II Electrical protection
L70 - 25,000Hrs
Available in White And Black Finish

Application

Lawns
Gardens
Pathways
Courtyard
Factories

Advantages

80% Energy Saving
Environmentally Safe
Less Heat produced
Innovative ,
Easy installation and long Life

Energising Tomorrow





TECHNICAL DATA		
Product Code	LBHR-20W (Round)	LBHO-20W (Oval)
Power	20W	20W
Voltage	86~265V AC	86~265V AC
Luminous Flux	1600 Lm	1600 Lm
Efficacy	80 Lm/W	80 Lm/W
Energy efficiency	A+	A+
CRI	> 80	> 80
Beam angle	120°	120°
Operating temperature	-20 °C to+40 °C	-20 °C to+40 °C
Storage temperature	Up to 50°C	Up to 50°C
Body Material	Poly Carbonate Body	Poly Carbonate Body
CCT	3000K / 6500K	3000K / 6500K
IP	65	65
Dimmable	No	No
Life Time	25,000Hrs	25,000Hrs
Cover	Frosted Diffuser	Frosted Diffuser
Finishing color	Black/White	Black/White
Mounting	Surface mounted	Surface mounted
Size in mm (LXWXH)	235X64 mm	260X130X64 mm




SPECTRAL TEST REPORT FOR LAMP

LBHR-20W

LBHO-20W


LUMINOUS INTENSITY DISTRIBUTION



LUMINOUS INTENSITY DISTRIBUTION



LUMINOUS INTENSITY DISTRIBUTION



LUMINOUS INTENSITY DISTRIBUTION

