



### Specification

- Pull rope type/Airflow initiated auto shutter rear baffle design can prevent outdoor air flow, mosquito enter.
- New design panel, large air volume low noise.
- Simple structure, easy to install.
- The motor is made of silicon steel sheet and copper material for long service life.
- Installed with overheat thermal protector for safer use.

### Application

- Bathroom
- Kitchen
- Shops




product code	size	power (W)	rated volt (V)	frequency (Hz)	volume(m3/h)	noise (dB)	Rpm (r/min)
15RS-J	6"-150MM	15	220~240V	50	168	38	1980
20RS-J	8"-200MM	25	220~240V	50	324	41	1920
15RS-A	6"-150MM	15	220~240V	50	135	38	1700
20RS-A	8"-200MM	25	220~240V	50	222	49	1800

\*Data subject to change without notice

### Features

- Sleek and stylish design
- Noiseless
- Sturdy Construction for long life
- Long life heavy duty motor
- Rubber fastner for quick mounting
- Made of special grade of plastic
- Thermal protection for the motor



Model	A	B	C	D
15RS-J	206	82	135	176
20RS-J	272	103	185	238
15RS-A	206	87	46	176
20RS-A	272	96	36	239



### Specification

- The blades are designed with five blades for high air volume and low noise.
- Automatic stop louvers to prevent mosquitoes from entering.
- Oil sink of front panel is easy to disassemble and easy to clean.
- The motor is made of silicon steel sheet and copper material for long service life.
- Installed with overheat thermal protector for safer use.

### Application

- Bathroom
- Kitchen
- Shops




product code	size	power (W)	rated volt (V)	frequency (Hz)	volume(m <sup>3</sup> /h)	noise (dB)	Rpm (r/min)
15SQ-J	6"-150MM	25	220~240V	50	258	40	1350
20SQ-J	8"-200MM	32	220~240V	50	486	41	1250
25SQ-J	10"-200MM	35	220~240V	50	750	42	1200

\*Data subject to change without notice

### Features

- Sleek and stylish design
- Noiseless
- Sturdy Construction for long life
- Long life heavy duty motor
- Made of special grade of plastic
- Thermal protection for the motor
- Airflow initiated auto shutter to prevent dust & mosquito enter.



Model	A	B	C	D
15SQ-J	237	37	82	162
20SQ-J	293	35	66	240
25SQ-J	338	35	77	290